



Polyester Round Sling



S. D. M.
Qualified Fittings

Lifting Round Sling Type PRS-1




WLL	Thickness	Width	Min	Max	Weight
kg	mm	mm	m	m	kg/m
1000	6	40	0.5	80	0.4
2000	7	50	0.5	80	0.61
3000	8	60	0.5	80	0.75
4000	9	70	0.5	80	0.8
5000	11	75	0.5	80	0.84
6000	12	80	1	80	0.98
8000	13	90	1	80	1.1
10000	15	100	2	80	2.2
12000	16	110	2	80	3.2
15000	18	125	2	80	3.8
20000	20	150	2.5	80	5.2
25000	24	180	2.5	80	6.5
30000	32	200	2.5	80	7.8
40000	40	200	2.5	80	10.4
50000	45	220	2.5	80	13
60000	65	220	4	80	15.6
80000	70	260	4	80	20.8
100000	80	290	4	80	25
200000	120	450	5	80	64
300000	160	525	5	80	79
400000	200	670	5	80	95.5
500000	220	750	8	80	113.4
600000	240	820	8	80	136
700000	260	870	8	80	152
800000	280	930	9	80	175
900000	300	990	9	80	199
1000000	320	1050	9	80	222

Lifting Round Sling Type PRS-2



WLL	Thickness	Width	Min	Max	Weight
kg	mm	mm	m	m	kg/m
1000	15	75	0.5	80	0.47
2000	16	95	0.5	80	0.6
3000	18	115	0.5	80	0.82
4000	20	135	0.5	80	1.2
5000	25	145	0.5	80	1.47
6000	27	155	1	80	1.7
8000	28	175	1	80	2.2
10000	29	195	2	80	3
12000	30	215	2	80	3.4
15000	31	240	2	80	4
20000	32	290	2.5	80	5.6
25000	34	350	2.5	80	6.8
30000	68	390	2.5	80	8.2
40000	75	490	2.5	80	10.9
50000	86	590	2.5	80	13.8
60000	126	280	4	80	16.6
80000	138	300	4	80	22
100000	152	320	4	80	27
200000	230	460	5	80	66
300000	310	535	5	80	82
400000	380	680	5	80	98
500000	410	760	8	80	116
600000	460	830	8	80	139
700000	498	880	8	80	155
800000	520	940	9	80	178
900000	580	1000	9	80	202
1000000	610	1060	9	80	226

Lifting Round Sling Type PRS-3



WLL	Thickness	Width	Min	Max	Weight
kg	mm	mm	m	m	kg/m
1000	11	40	1	80	0.36
2000	12	50	1	80	0.53
3000	14	60	1	80	0.67
4000	15	70	2	80	0.73
5000	23	75	2	80	1.1
6000	25	80	2	80	1.25
8000	26	90	3	80	1.9
10000	27	100	3	80	2.5
12000	28	110	3	80	2.8
15000	29	150	3	80	3.6
20000	31	180	3	80	4.8
25000	34	200	3	80	5.5
30000	36	220	4	80	8
40000	40	250	4	80	12.2
50000	46	300	4	80	15.8

Lifting Round Sling Type PRS-4



WLL	Thickness	Width	Min	Max	Weight
kg	mm	mm	m	m	kg/m
1000	7	75	1.2	80	0.34
2000	8	95	1.3	80	0.38
3000	9	115	1.4	80	0.5
4000	10	135	1.5	80	0.75
5000	12	145	1.6	80	1.2
6000	13	155	1.7	80	1.4
8000	15	175	1.8	80	1.6
10000	17	195	1.9	80	2
12000	18	215	2.1	80	2.9
15000	22	240	2.3	80	3.2
20000	24	290	2.5	80	3.9
25000	28	350	2.9	80	5.3
30000	32	390	3.3	80	6.6
40000	40	490	3.7	80	7.9
50000	45	590	4.1	80	10.5